

**SDS** Safety Data Sheet

> Version 01.01.01 Updated 08.04.24

## **VITRAFIX SARKING TAPE VWST25**

FV.COM.AU

Section 1: Identification of the substance/ mixture and of the company/ undertaking

Product description: LDPEco black film, single-sided adhesive with modified acrylic dispersion, paper liner Product name: Vitrafix Sarking Tape by Fairview

Uses of the substance or mixture:
Main user group: SU3, SU21 and SU22
Product category PC1 (adhesives, sealants)

Use the self-adhesive LDPEco Process category: PROC 10

Producer: Fairview

Address: 18-20 Donald St, Lithgow, NSW 2790

Tel: 1800 007 175

Email: marketing@fv.com.au

Web: fv.com.au

Section 2: Hazards identification

#### Classification of the substance or mixture:

Not a hazardous product.

#### Label elements:

The product does not need to be labelled.

# Section 3: Composition/information on ingredients

#### Chemical characterization:

Adhesive on acrylic acid ester copolymer.

#### **Hazardous ingredients:**

No hazardous materials content.

#### Section 4: First-aid measures

#### Inhalation:

No special measures necessary.

#### Skin contact:

Wash with water and soap as a precaution. If skin irritation persists, call a physician.

#### Eye contact:

Rinse with plenty of water. If eye irritation persists, consult a specialist.

#### Ingestion:

Drink 1 or 2 glasses of water. Consult a physician if necessary.

#### Section 5: Firefighting measures

Suitable extinguishing media: Water, CO<sup>2</sup>, foam, powder.

**Special hazards arising from the substance or mixture:** No known information.

Special protective equipment: No.

#### Section 6: Accidental release measure

**Personal precautions:** Avoid contact with the body.

**Environmental precautions:** Mechanical recording. Do not allow undiluted product or large quantities of it to reach groundwater, watercourse or sewage system.

#### Section 7: Handling and storage

**Handling:** No special measures required.

Fire protection: No special measures required.



**SDS** Safety Data Sheet

> Version 01.01.01 Updated 08.04.24

## **VITRAFIX SARKING TAPE VWST25**

FV.COM.AU

Storage: At room temperature of about 21°C and 50% RH.

Section 8: Exposure control and personal protection

#### Components:

Not contain any substances for which an occupational exposure limit value are set.

#### Personal protection:

#### Eye/ face protection:

Safety glasses with side-shields.

#### Hand protection:

Suitable protective gloves.

#### Section 9: Physical and chemical properties

#### 9.1 Information on basic physical and chemical properties

# Appearance Solid Colour Black Odour Weak characteristic odour PH Density

Section 10: Stability and reactivity

General: Stable.

Possibility of hazardous reactions:

No dangerous reactions known.

Hazardous decomposition products:

No data available.

Section 11: Toxicological information

There is no information.

Section 12: Ecological information

**Ecotoxicity:** Poorly biodegradable.

Additional information: No water hazard

Section 13: Disposal consideration

Disposal according to official regulations.

Section 14: Transport information

No hazardous good according to transport regulations.

Section 15: Regulatory information

**EU regulations:** No.

National regulations: No.

**Chemical Safety Assessment:** For this product was not Chemical safety assessment performed.



**SDS**Safety Data Sheet

Version 01.01.01 Updated 08.04.24

FV.COM.AU

# **VITRAFIX SARKING TAPE VWST25**

#### Section 16: Other information

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Department issuing MSDS: Department technical laboratory/development.