

VITRAFIX SARKING TAPE VWST25

FV.COM.AU

Product Description

Vitrafix Sarking Tape by Fairview is a black, single-sided, acrylic tape with high UV resistance.

Product Application

Used to seal overlaps on breathable membranes, along with joints and penetrations.

Product Specifications

Roll Size	75mm x 25m
Colour	Black

Technical Data

Adhesive Carrier	LDPEco Film, Black, Reinforced with Scrim
Adhesive System	Acrylic Dispersion
Release Liner	Silicone-Coated Paper, Brown
Thickness, Without Liner	0.30 – 0.33 mm
Peel Adhesion	≥ 35 N/25 mm
Elongation	≥ 25 N/25 mm; 300 %
Processing Temperature	+5 °C recommended, processable from -10 °C
Temperature Resistance	-30 °C to +100 °C
Tack	Excellent
Condensation Water Resistance	High
Ageing Resistance	2 Years UV Resistance (Exposed)



vitrafix[™]

FAÇADE SYSTEM ACCESSORIES / BY FAIRVIEW

Weatherproofing

TDS

Technical Data Sheet

Version 01.01.01
Updated 08.04.24

VITRAFIX SARKING TAPE VWST25

FV.COM.AU

Additional Important Information

- It is the responsibility of the user to test for compatibility.
- Fairview reserves the right to alter product specifications without prior notice, in line with its company policy of continuous development and improvement.
- Consult the Fairview Team for the latest version of the TDS, or with any other queries.