

TDS

Technical Data Sheet

Version 01.01.01 Updated 08.04.24

VITRAFIX DOUBLE SIDED SARKING TAPE VWSTD100

FV.COM.AU

Product Description

Vitrafix Double Sided Sarking Tape by Fairview is a white, double-sided, acrylic tape with high bonding properties.

Product Specifications

Roll Size 50mm x 100m

Colour White

Product Applications

Used to bond breathable membranes to the façade.

Technical Data

Adhesive Carrier	Polyester Scrim
Adhesive System	Acrylic Dispersion
Release Liner	Silicone-Coated Filmic Liner, White
Thickness, Without Liner	0.22 – 0.24 mm
Peel Adhesion	≥ 30 N/25 mm
Sheer Adhesion	100g / 625mm²
Processing Temperature	+5 °C recommended, processable from -10 °C
Temperature Resistance	-30 °C to +100 °C
Tack	Excellent
Condensation Water Resistance	High
Ageing Resistance	Very high



TDS

Technical Data Sheet

Version 01.01.01 Updated 08.04.24

VITRAFIX DOUBLE SIDED SARKING TAPE VWSTD100

FV.COM.AU

Additional Important Information

- It is the responsibility of the user to test for compatibility.
- Fairview reserves the right to alter product specifications without prior notice, in line with its company policy of continuous development and improvement.
- Consult the Fairview Team for the latest version of the TDS, or with any other queries.