

VITRAFIX WALL SARKING ULTRA VWSU30

FV.COM.AU

Product Description

Vitrafix Wall Sarking Ultra by Fairview is a vapour permeable membrane used for commercial and domestic walling applications to resist the passage of water and dust etc into the fabric of the building.

Whilst providing a barrier to the effects of weathering, the membrane also allows harmful vapour to escape which minimises the risk of condensation and mould growth.

Vitrafix Wall Sarking Ultra is highly resistant to UV and can be left exposed for up to 6 months to facilitate the installation schedule of your project.

Product Specifications

Widths	1.5m
Lengths	30m
Thickness	0.7mm

Technical Data

Weight per roll	7.2kg
UV exposure	6 months
Duty Classification	Light Duty
Vapour Classification	Class 4, Vapour Permeable
Vapour Permeability	1.812 g/N.s
Water Control Classification	Water Barrier
Flammability Index	Low – 4
Electrical Conductivity	Non-Conductive
Emittance Value	0.86
Emittance Classification	Non-Reflective
Emittance Category	NN
AWTA test report	AS/NZS 4201 classification report no. 22-000249
AWTA test report	AS 1530.2 Flammability Index report no. 22.000250

Additional Important Information

- » Fairview Wall Sarking Ultra can be used on walls and roofs in accordance with the duty classification. It satisfies section 3.10 of AS 3959 with a flammability index of less than 5 when tested in accordance with AS 1530.2.